

## Field mount Indicators for safe and hazardous areas



### Robust and user-friendly!

The F-Series is a robust range of field mount indicators, controllers and monitoring systems for industrial environments. It is so rugged, you can even stand on it! Once familiar with an F-Series product, you can program ALL models in ALL series without a manual: “know one, know them all”

### Inputs

- ☑ Reed-switch, NAMUR, NPN/PNP pulse, Sine wave (coil), Active pulse signals, PT100 or (o)4 - 20mA / 0 - 10V DC analog inputs.

### Outputs

- ☑ Configurable pulse, alarm or control outputs.
- ☑ Analog (o)4 - 20mA output.
- ☑ Modbus or HART communication.

### Applications

- ☑ The F-Series is your first and best choice for field mount indicators in safe and hazardous area applications. Especially in harsh weather conditions like rain, snow, salty atmospheres and temperatures between -40°C up to +80°C (-40°F up to 176°F).

### Features

- ☑ Intrinsically Safe available according ATEX, IECEx, FM and CSA for gas and dust applications.
- ☑ Robust IP67 (Type4X) field enclosure, you can even stand on it!
- ☑ “know one, know them all” configuration structure.
- ☑ Easy configuration with clear alphanumeric display.
- ☑ Very diverse mounting possibilities: walls, pipes, panels or directly onto outdoor sensors!
- ☑ Fully integrated HART communication protocol.
- ☑ Displays flow rate, totals, level, temperature, pressure, percentage and alarm values with various selectable engineering units.
- ☑ Clear 17mm(0.7”) numeric digits and 8mm(0.3”) alphanumeric digits.
- ☑ LED backlight, can be set to be red flashing in case of an alarm.
- ☑ Piegraph indication and 5 1/2 extra large 26mm (1”) digits with the basic models.
- ☑ Selectable on-screen engineering units; volumetric or mass.
- ☑ Auto backup of settings and running totals.
- ☑ Power requirements: long life lithium battery, 8 - 24V AC/DC, 110 - 230V AC or input / output loop powered.
- ☑ Sensor supply: 1.2 / 3 / 8.2 / 12 / 24V DC.

# Leaflet F-Series

So robust, you can even stand on it!



*Count on us.*

## F-Series feature overview



### Very easy menu structure



### Clear alarm messages and flashing display



### Very diverse mounting possibilities



### Resistant to harsh weather conditions



Quality  
ISO 9001  
[www.dekra.nl](http://www.dekra.nl)

Fluidwell bv  
P.O. Box 6 • 5460 AA • Veghel  
Voltaweg 23 • 5466 AZ • Veghel  
The Netherlands

Telephone: +31 (0) 413 - 343 786  
Telefax: +31 (0) 413 - 363 443  
Email: [displays@fluidwell.com](mailto:displays@fluidwell.com)  
Internet: [www.fluidwell.com](http://www.fluidwell.com)



Specifications are subject to change without notice.  
Copyright: Fluidwell bv - 2016 - F-SERIES-LEAFLET-EN-V1633